

where

$$T = [A_b^p e_1, \dots, A_b e_1, I_m]$$

$$A_b = \begin{bmatrix} -b_{m-1}/b_m & & & I_{m-1} \\ -b_0/b_m & 0 & \dots & 0 \end{bmatrix}. \quad (99)$$

It is readily verified that

$$Tb = 0, \quad TA = A_b T + T A^p b e_1^T. \quad (100)$$

Therefore, from (74) and (78) we obtain

$$\dot{\bar{x}} = A_b \bar{x} + T[A^p b y + \varphi(y)] \quad (101)$$

$$\dot{\tilde{x}} = A_b \tilde{x} + T(A^p b - K_0) \tilde{x}_1. \quad (102)$$

These two systems have asymptotically stable homogeneous parts with inputs  $y, \tilde{x}_1 \in \mathcal{M}(|X(0)|, \mu)$ . This proves that  $\bar{x}, \tilde{x} \in \mathcal{M}(|X(0)|, \mu)$ . So, from (98), we have  $x, \tilde{x} \in \mathcal{M}(|X(0)|, \mu)$ , and therefore,  $\hat{x} \in \mathcal{M}(|X(0)|, \mu)$ . Thus,  $u \in \mathcal{M}(|X(0)|, \mu)$ , and consequently,  $\xi \in \mathcal{M}(|X(0)|, \mu)$ . Hence

$$|X(t)| \leq \rho_0(|X(0)|)e^{-dt} + \rho_\mu(\mu) \quad (103)$$

where  $\rho_0$  and  $\rho_\mu$  are locally Lipschitz class  $\mathcal{K}_\infty$  functions. The proof of global asymptotic stability is the same as in Theorem 3.1. We first rewrite the closed-loop system

$$\begin{aligned} \dot{x} &= Ax + \varphi(x_1) + b\sigma(x_1)u(x_1, \hat{x}, \zeta, m) \\ &\quad + \mu b[c_\Delta \xi + q\sigma(x_1)u(x_1, \hat{x}, \zeta, m)] \\ \dot{\hat{x}} &= A_0 \hat{x} + K_0 x_1 + \varphi(x_1) + b\sigma(x_1)u(x_1, \hat{x}, \zeta, m) \\ \dot{\zeta} &= A_0 \zeta + K_0 x_1 + \varphi(x_1) \\ \dot{\xi} &= A_\Delta \xi + b_\Delta \sigma(x_1)u(x_1, \hat{x}, \zeta, m) \\ \dot{m} &= -\delta m + |\hat{x}_2 - \zeta_2|_e \end{aligned}$$

in the form (66) and then proceed as in the proof of Theorem 3.1.  $\square$

#### APPENDIX

*Definition A.1:* The system  $\dot{x} = f(t, x, u)$  is said to be input-to-state practically stable (ISpS) if there exist a class  $\mathcal{KL}$  function  $\beta$ , a class  $\mathcal{K}$  function  $\gamma$ , and a positive real number  $d$  such that for any  $x(0)$  and for any input  $u(\cdot)$  continuous on  $[0, \infty)$ , the solution exists for all  $t \geq 0$  and satisfies  $|x(t)| \leq \beta(|x(s)|, t - s) + \gamma(\sup_{s \leq \tau \leq t} |u(\tau)|) + d$  for all  $0 \leq s \leq t$ .

#### REFERENCES

- [1] B. R. Barmish, M. Corless, and G. Leitmann, "A new class of stabilizing controllers for uncertain dynamical systems," *SIAM J. Contr. Optim.*, vol. 21, pp. 246-255, 1983.
- [2] M. Corless, "Control of uncertain nonlinear systems," *J. Dynamic Systems, Measurement, Contr.*, vol. 115, pp. 362-372, 1993.
- [3] R. A. Freeman and P. V. Kokotović, "Design of 'softer' robust nonlinear control laws," *Automatica*, vol. 29, pp. 1425-1437, 1993.
- [4] ———, "Global robustness of nonlinear systems to state measurement disturbances," in *Proc. 32nd IEEE Conf. Decision Contr.*, pp. 1507-1512, 1993.
- [5] W. Hahn, *Stability of Motion*. New York: Springer-Verlag, 1967.
- [6] Z. P. Jiang and L. Praly, "Preliminary results about robust Lagrange stability in adaptive nonlinear regulation," *Int. J. Adaptive Contr. Signal Processing*, vol. 6, pp. 285-307, 1992.

- [7] ———, "Technical results for the study of robustness of Lagrange stability," *Syst. Contr. Lett.*, vol. 23, pp. 67-78, 1994.
- [8] Z. P. Jiang, A. R. Teel, and L. Praly, "Small-gain theorem for ISS systems and applications," *Math. Contr., Signals, Syst.*, vol. 7, pp. 95-120, 1995.
- [9] I. Kanellakopoulos, P. V. Kokotović, and A. S. Morse, "A toolkit for nonlinear feedback design," *Syst. Contr. Lett.*, vol. 18, pp. 83-92, 1992.
- [10] H. Khalil, *Nonlinear Systems*. New York: Macmillan, 1992.
- [11] ———, "Robust servomechanism output feedback controllers for a class of feedback linearizable systems," in *Proc. 12th IFAC World Congr.*, vol. 8, pp. 35-38, 1993.
- [12] M. Krstić, I. Kanellakopoulos, and P. V. Kokotović, *Nonlinear and Adaptive Control Design*. New York: Wiley, 1995.
- [13] M. Krstić, J. Sun and P. V. Kokotović, "Control of feedback linearizable systems with input unmodeled dynamics," in *Proc. 33rd IEEE Conf. Decision Contr.*, pp. 1633-1638, 1994.
- [14] R. Marino and P. Tomei, "Global adaptive output-feedback control of nonlinear systems, Part II: Nonlinear parameterization," *IEEE Trans. Automat. Contr.*, vol. 38, pp. 33-49, 1993.
- [15] R. Marino and P. Tomei, "Robust stabilization of feedback linearizable time-varying uncertain nonlinear systems," *Automatica*, vol. 29, pp. 181-189, 1993.
- [16] L. Praly, "Commande adaptive indirecte multivariable," in *Proc. Colloque National du CNRS, Belle-Ile*, 1982.
- [17] L. Praly and Z. P. Jiang, "Stabilization by output-feedback for systems with ISS inverse dynamics," *Syst. Contr. Lett.*, vol. 21, pp. 19-33, 1993.
- [18] Z. Qu, "Robust control of nonlinear uncertain systems under generalized matching conditions," *Automatica*, vol. 29, pp. 985-998, 1993.
- [19] ———, "Model reference robust control of SISO systems with significant unmodeled dynamics," in *Proc. 1993 ACC*, pp. 255-259.
- [20] ———, "Model reference robust control of weakly nonminimum phase systems," in *Proc. 32nd IEEE Conf. Decision Contr.*, San Antonio, TX, pp. 996-1001, 1993.
- [21] J.-J. E. Slotine and J. K. Hedrick, "Robust input-output feedback linearization," *Int. J. Contr.*, vol. 57, pp. 1133-1139, 1993.
- [22] E. D. Sontag, "Smooth stabilization implies coprime factorization," *IEEE Trans. Automat. Contr.*, vol. 34, pp. 435-443, 1989.
- [23] A. R. Teel and L. Praly, "On output-feedback stabilization for systems with ISS inverse dynamics and uncertainties," in *Proc. 32nd IEEE Conf. Decision Contr.*, San Antonio, TX, pp. 1942-1947, 1993.

## Correction to "Adaptive Control of Robot Manipulators with Flexible Joints"

B. Brogliato and R. Lozano

#### I. INTRODUCTION

The above paper<sup>1</sup> contains two flaws that were recently brought to our attention by Hsu [1]. 1) The first mistake concerns the definition of the signal  $q_{2d}$  in (6) and (C.20): At time  $t = 0$ , the term  $q_{2d}(0)$  appears on both sides of the equalities in (6) and (C.20). Hence the initial conditions on the state and on the desired trajectory  $q_{1d}$  and its

Manuscript received May 1, 1995; revised October 29, 1995. This work was supported in part by the Commission of European Communities under Contract ERB CHRX CT 93-0380.

B. Brogliato is with the Laboratoire d'Automatique de Grenoble, URA C.N.R.S. 228, B.P. 46, 38402 Saint Martin d'Hères, France.

R. Lozano is with the Université de Technologie de Compiègne, URA C.N.R.S. 817, BP 649, 60206 Compiègne, France.

Publisher Item Identifier S 0018-9286(96)03725-7.

<sup>1</sup>R. Lozano and B. Brogliato, *IEEE Trans. Automat. Contr.*, vol. 37, pp. 174-181, Feb. 1992.

first and second derivatives are constrained. 2) The second mistake is that the regressor matrix  $Y_4$  in (C.18) contains integral terms which are not shown to be bounded. Consequently, the stability analysis in Appendix C [(C.42)–(C.47)], based on some signal chasing, is not complete.

- Concerning point 1), it has been shown in [2] that the positive definite function  $V$  in (3) can be modified to

$$V = \frac{1}{2}v_1^T D(q_1)v_1 + \frac{1}{2}v_2^T J_m v_2 + \frac{1}{2}(\tilde{q}_1 - \tilde{q}_2)^T K(\tilde{q}_1 - \tilde{q}_2) \quad (1)$$

so that  $q_{2d}$  is now defined as (see [2, (23)])

$$q_{2d} = q_{1d} + K^{-1}(D(q_1)\ddot{q}_{1r} + C(q_1, \dot{q}_1)\dot{q}_{1r} + g(q_1) - B_1 v_1) \quad (2)$$

where  $B_1 = B_1^T > 0$  is a constant feedback gain. This allows us to remove the constraint on the initial conditions and to prove exponential Lyapunov stability of the fixed parameters scheme; see [2]. In the adaptive case, the signal  $q_{2d}$  in (C.20) can be modified as well to avoid the initial conditions' constraints problem. Indeed the term  $K \int_0^t (v_1 - v_2) dt$  in the right-hand side of (C.1) is replaced by  $K(\tilde{q}_1 - \tilde{q}_2)$ . Then  $w_5$  in (C.2), (C.5), and (C.20) is modified to  $w_5 = -q_{1d}$ . This does not affect the definition of the other terms in (C.20) since only  $w_5$  has been modified.

Another possible solution was suggested to us [1], presented here in the nonadaptive case (compare with [3, (3) and (6)])

$$V = \frac{1}{2}v_1^T D(q_1)v_1 + \frac{1}{2}v_2^T J_m v_2 + \frac{1}{2}z^T K z \quad (3)$$

where  $z$  and  $q_{2d}$  are defined as

$$q_{2d} = q_{1d} - \lambda x + K^{-1}(-v_1 + D(q_1)\ddot{q}_{1r} + C(q_1, \dot{q}_1)\dot{q}_{1r} + g(q_1)) \quad (4)$$

$$\dot{q}_{1r} := \dot{q}_{1d} - \lambda \tilde{q}_1 \quad (5)$$

$$\dot{x} := \tilde{q}_1 - \tilde{q}_2 \quad (6)$$

$$z = \lambda x + (\tilde{q}_1 - \tilde{q}_2) \quad (\dot{z} = v_1 - v_2) \quad (7)$$

$$u = -v_2 - J_m[-\ddot{q}_{2d} + \lambda \dot{\tilde{q}}_2] - K[q_{1d} - q_{2d} - \lambda x]. \quad (8)$$

*Proof:* Consider  $V(v_1, v_2, z)$  as given by (3). Differentiating (3) we obtain

$$\dot{V} = v_1^T [D\dot{v}_1 + C v_1 + K z] + v_2^T [J_m v_2 - K z] \quad (9)$$

where we have used property P3 of [3] and the fact that [from (6) and (7)]  $\dot{z} = v_1 - v_2$ . Now, closely following [3, Appendix B]

$$D\dot{v}_1 + C v_1 + K z = \quad (10)$$

$$-g - K(q_1 - q_2) + D[-\dot{q}_{1d} + \lambda \dot{q}_1] + C[-\dot{q}_{1d} + \lambda \dot{q}_1] + K z = \quad (11)$$

$$-g - K(q_1 - q_2) + D[-\dot{q}_{1d} + \lambda \dot{q}_1] + C[-\dot{q}_{1d} + \lambda \dot{q}_1] \quad (12)$$

$$+ K[\lambda x + (q_1 - q_2) - (q_{1d} - q_{2d})] = \quad (12)$$

$$K q_{2d} + \{-g - D\dot{q}_{1r} - C\dot{q}_{1r} - K[\lambda x - q_{1d}]\}. \quad (13)$$

The last term within braces is the new  $w_1$ , using the notation of Appendix B of the original paper. From (4), obtained by requiring the expression in (13) to be equal to  $-v_1$ , we then have

$$\dot{V} = -v_1^T v_1 + v_2^T [J_m v_2 - K(\lambda x + (\tilde{q}_1 - \tilde{q}_2))]. \quad (14)$$

The last term within brackets is the new  $w_2$ , following our original notation. After some manipulations using the robot motor equations, one gets

$$w_2 = u + J_m[-\ddot{q}_{2d} + \lambda \dot{\tilde{q}}_2] + K[q_{1d} - q_{2d} - \lambda x]. \quad (15)$$

Then, as in [3], setting  $w_2 = -v_2$ , one obtains (8). Consequently, the proposed control law yields (as in [3])

$$\dot{V} = -v_1^T v_1 - v_2^T v_2 \quad (16)$$

which is semi-definite negative as required.

- Concerning point 2): Fundamentally, the flaw comes from the fact that to be able to define signals  $q_{2d}$ ,  $\dot{q}_{2d}$  which are measurable and  $\ddot{q}_{2d}$  that does not depend on  $\ddot{q}_2$  (so that the control input in (14) is well defined), we need to filter the first dynamical equation (1) to suitably parameterize  $Dv_1$  in (C.18). In the above paper we filtered (1) with an integrator, hence the possible unboundedness of the regressor  $Y_4$  in (C.18). We now propose to use a first-order filter with transfer function  $\frac{1}{s+1}$  instead of the integrator.

Applying the filter to (1) one gets (we drop the arguments for convenience)

$$\frac{1}{s+1} \{D\dot{q}_1 + C\dot{q}_1 + g + K(q_1 - q_2)\} = 0. \quad (17)$$

Now we have

$$\frac{1}{s+1} \{D\dot{q}_1\} = D\dot{q}_1 - D(0)\dot{q}_1(0) - \frac{1}{s+1} \times \{D\dot{q}_1 - D(0)\dot{q}_1(0)\} - \frac{1}{s+1} \{\dot{D}\dot{q}_1\}. \quad (18)$$

Indeed (18) can be obtained by first noting that  $D\dot{q}_1 = \frac{d}{dt}(D\dot{q}_1) - \dot{D}\dot{q}_1$ . Now

$$\frac{1}{s+1} \{D\dot{q}_1\} = \int_0^t e^{-(t-\tau)} D\dot{q}_1 d\tau. \quad (19)$$

Then using integration by parts one gets

$$\begin{aligned} \frac{1}{s+1} \{D\dot{q}_1\} &= e^{-t} \left[ e^{\tau} \left( D\dot{q}_1 - D(0)\dot{q}_1(0) - \int_0^{\tau} \dot{D}\dot{q}_1 dy \right) \right]_0^t \\ &\quad - \int_0^t e^{\tau} \left( D\dot{q}_1 - D(0)\dot{q}_1(0) - \int_0^{\tau} \dot{D}\dot{q}_1 dy \right) d\tau \end{aligned} \quad (20)$$

which finally yields

$$\begin{aligned} \frac{1}{s+1} \{D\dot{q}_1\} &= D\dot{q}_1 - D(0)\dot{q}_1(0) - \int_0^t \dot{D}\dot{q}_1 d\tau - \int_0^t e^{-(t-\tau)} \\ &\quad \times \left( D\dot{q}_1 - D(0)\dot{q}_1(0) - \int_0^{\tau} \dot{D}\dot{q}_1 dy \right) d\tau. \end{aligned} \quad (21)$$

Using the fact that (still integrating by parts)

$$\begin{aligned} \int_0^t e^{-(t-\tau)} \dot{D}\dot{q}_1 d\tau &= \int_0^t \dot{D}\dot{q}_1 d\tau - \int_0^t e^{-(t-\tau)} \left( \int_0^{\tau} \dot{D}\dot{q}_1 dy \right) d\tau \end{aligned} \quad (22)$$

we then get (18) by combining (21) and (22).

Now from (17) and (18) we have

$$\begin{aligned} D\dot{q}_1 &= D(0)\dot{q}_1(0) + \frac{1}{s+1}\{D\dot{q}_1 - D(0)\dot{q}_1(0)\} \\ &+ \frac{1}{s+1}\{\dot{D}\dot{q}_1\} - \frac{1}{s+1}\{C\dot{q}_1 + g + Kq_1\} \\ &+ \frac{1}{s+1}\{Kq_2\}. \end{aligned} \quad (23)$$

The terms between brackets can be written as  $Y_i(q_1, \dot{q}_1)\theta_i$  for some constant vector  $\theta_i$ . Hence  $\frac{1}{s+1}\{Y_i(q_1, \dot{q}_1)\theta_i\} = \frac{1}{s+1}\{Y_i(q_1, \dot{q}_1)\}\theta_i \triangleq Y_{if}\theta_i$  with  $\dot{Y}_{if} + Y_{if} = Y_i(q_1, \dot{q}_1)$ .

It follows that (C.18) can be written as

$$Dv_1 = Y_{4f}\theta_4 \quad (24)$$

with  $\dot{Y}_{4f} + Y_{4f} = Y_4$  for some  $Y_4(q_1, \dot{q}_1, q_2)$ . Note also that  $q_{2d}, \dot{q}_{2d}$  in (C.20) can be computed from position and velocities measurements only which is crucial for the algorithm to be implementable. From the new parameterization, it follows that if  $q_1, \dot{q}_1$  and  $q_2$  are bounded, so is  $Y_4$ . This was not the case when integrators were used.

The stability analysis is much simplified. Note first that the modification of  $Y_4\theta_4$  leaves the rest of the analysis and algorithm unchanged. Hence from (C.41),  $q_1$  and  $\dot{q}_1$  are bounded. From (23) it follows that  $q_{2f} = \frac{1}{s+1}\{q_2\}$  is bounded. Hence from (C.20)  $q_{2d}$  is bounded, and consequently  $q_2$  and  $\dot{q}_1$  are bounded. Boundedness of  $\dot{q}_2$  follows by differentiating (C.20) which proves that  $\dot{q}_{2d}$  is bounded. Hence from (C.41)  $\dot{q}_2$  is bounded. Boundedness of  $u$  can be inferred by inspecting (C.27) and (C.32). Consequently  $\ddot{q}_2$  is bounded also.

#### REFERENCES

- [1] L. Hsu, private correspondence, COPPE/Federal Univ., Rio de Janeiro, Brazil, Mar. 1995.
- [2] B. Brogliato, R. Ortega, and R. Lozano, "Global tracking controllers for flexible joint manipulators: A comparative study," *Automatica*, vol. 31, no. 7, pp. 941-956, 1995.
- [3] R. Lozano and B. Brogliato, "Adaptive control of robot manipulators with flexible joints," *IEEE Trans. Automat. Contr.*, vol. 37, pp. 174-181, Feb. 1992.

### Comments on "Control of Vector Discrete-Event Systems II—Controller Synthesis"

Zhengyi Zhao

**Abstract**—This paper notes that the proof of Appendix 7 in the above paper<sup>1</sup> is wrong. A counterexample is given.

#### I. INTRODUCTION

In the proof of Appendix 7 of the above paper,<sup>1</sup> the following conclusion was used: To maximize  $v_{1,1} \sim \sum_{(i,j) \in D} v_{i,j}, v_{i,j}$  for

Manuscript received May 8, 1995.

The author is with the Research Institute of Automation, Southeast University, 210096, P.R. China.

Publisher Item Identifier S 0018-9286(96)04367-X.

<sup>1</sup>Y. Li and W. M. Wonham, "Control of vector discrete-event systems II—Controller synthesis," *IEEE Trans. Automat. Contr.*, vol. 39, pp. 512-531, 1994.




Fig. 1. A tree structure of TS2.

$(i, j) \in D$  should be set to be as large as possible. This conclusion is wrong.

#### II. A COUNTEREXAMPLE

Fig. 1 is a TS2

$$E = \begin{bmatrix} -1 & 1 & 0 \\ 0 & -1 & 1 \\ 0 & 0 & -1 \end{bmatrix}, \quad B = [1, -1, -1].$$

The following special type of LIP:

$$\text{s.t. } \begin{cases} \max BV \\ EV \geq -X \\ V \geq 0 \end{cases}$$

has a solution

$$V^* = [x_{1,1}, 0, 0]^T$$

and

$$\begin{aligned} BV^* &= [1, -1, -1][x_{1,1}, 0, 0]^T \\ &= x_{1,1}. \end{aligned}$$

According to the conclusion mentioned above,<sup>1</sup>  $v_{1,1}, v_{1,2}, v_{1,3}$  should be set to be as large as possible, that is

$$\hat{V} = [x_{1,1} + x_{1,2} + x_{1,3}, x_{1,2} + x_{1,3}, x_{1,3}]^T.$$

But

$$\begin{aligned} B\hat{V} &= x_{1,1} - x_{1,3} \\ &\leq BV^*. \end{aligned}$$

So it is shown that the proof of Appendix 7<sup>1</sup> is incorrect.

Authors' Reply by Y. Li and W. M. Wonham

The result of Appendix 7<sup>1</sup> is correct, and its proof<sup>1</sup> is intentionally sketchy. However, without further clarification, the statement of the "basic idea" in the proof is indeed unclear and can lead to an incorrect conclusion. We thank Zhao for noting this. A complete proof is now provided in the following.

As in Fig. 4,<sup>1</sup> we arrange the events and state variables of a TS2  $\mathcal{G}$  into levels as shown in Fig. 1. Denote the set of events in the TS2 as  $\Sigma$  and the set of state variables as  $\Omega$ . Let  $Z$  be the set of integers. Define the index set

$$D = \{(i, j) \mid B(\alpha_{i,j}) < 0\}.$$

Manuscript received June 30, 1995; revised November 13, 1995.

The authors are with the Department of Electrical and Computer Engineering, University of Toronto, Toronto, M5S1A4 Canada.

Publisher Item Identifier S 0018-9286(96)04368-1.